



Part number	Dimension(mm)						
	A	B	C	D	E	F	l min.
CUT1811	18.0±0.4	15.1±0.3	7.4±0.15	11.9±0.2	7.4±0.2	10.5±0.1	11.2
CUT2511	25.3±0.75	20.9±0.4	8.8±0.25	15.20±0.3	7.5±0.5	11.1±0.5	16.6
CUT3019	30±0.5	25.4±0.4	13.3±0.2	20.3±0.25	13.2±0.2	18.8±0.2	18.2
CUT3314	33.2±0.5	26.8±0.4	13.4±0.2	23.7±0.3	8.4±0.3	13.8±0.3	17.8
CUT3319	33.2±0.5	26.8±0.4	13.4±0.2	23.7±0.3	13.0±0.3	18.6±0.3	17.8
CUT4025	39.8±0.5	33.2±0.5	16.0±0.25	28.3±0.35	17.8±0.4	25.0±0.4	20
CUT4027	39.8±0.5	33.2±0.5	16.0±0.25	28.3±0.35	19.8±0.4	27.0±0.4	20

CUT Cores

For compact transformer
 Low distortion broadband transmission
 at low signal modual
 DC/DC converters

Part number	C1 (mm ⁻¹)	Le (mm)	Ae (mm ²)	Ve (mm ³)	Weight (g)/set	SM023	SM024
						AL(nH/N ²)±25%	
CUT1811	0.77	28.7	37.2	1067.64	6.5		
CUT2511	0.59	35.60	60.10	2140.00	11.20	2800	
CUT3019	0.41	49.50	120.00	5940.00	31.00	4000	4000
CUT3314	0.29	42.60	145.00	6177.00	29.60	5500	
CUT3319	0.35	51.40	147.40	7576.00	38.00	5200	5200
CUT4025	0.36	66.60	185.00	12321.00	72.00	5600	
CUT4027	0.35	71.30	205.00	14616.50	74.00	7500	

*All specification are subject to change without notice.